

REPLACEMENT ABSTRACT**ABSTRACT OF THE DISCLOSURE**

A SONET multiplexed system architecture that permits greater levels of integration. The architecture includes a time slot interchanger for routing information from at least one SONET input signal path associated with a respective first time slot to at least one SONET output signal path associated with a respective second time slot. Each input signal path includes a pointer interpreter, and each output signal path includes a FIFO buffer serially coupled to a pointer generator. The architecture further includes a synchronization buffer in each input signal path for transferring the input signal to the clock rate of the time slot interchanger. The architecture permits greater levels of integration when the time slot interchanger has more inputs than outputs, and/or the time slot interchanger provides the output signal to a pointer processor to transfer the output signal to the clock rate of the output signal path.

BEST AVAILABLE COPY

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.